SHAKER

VIBROMIX 50

MAIN FEATURES:

- > Robust and Stable Construction
- > Different platforms and Clamps
- > Compact shaking unit can be mounted separately in incubators
- > Orbital shaking, 25 mm orbit
- > Designed for heavy loads and continuous operation

Vibromix 50 is a large bench-top shaker designed for continuous run and heavy loads. This solidly constructed shaker has a housing that is made from coated steel plate to reduce motor noise and ensure stability. A powerful brushless motor and counter-weight shaking mechanism provides smooth operation and years of maintenance free use.



User friendly

The shaker speed is variable over the whole range, while operation can be set as timed or continuous. Both time and speed are set digitally. Setting the parameters is easy using a single encoder knob. Values are shown on the large, three digit LED display.

Applications

Vibromix 50 is suitable for temperature-controlled environments, making it ideal for cold rooms or use in heating incubators.

The universal platform for Erlenmeyer flasks is ideal for growing microbiological cultures.



TECHNICAL SPECIFICATIONS				
Model	VIBROMIX 50			
Code no.	621.000 or 1621.000			
Voltage	115V / 230V 50 - 60Hz			
Power	250VA			
Drive	Brushless DC Motor			
Speed range/ increment	50 to 400 rpm / 1 rpm			
Motion	Orbital, 25mm orbit			
Timer	0 to 99 min / in steps of 1 sec or continous			
Ambient operating temperature	4°C to 75°C			
Max. load	25kg			
Net weight	48kg			
Dimensions	600 x 550 x 150mm			

Flask volume	Platform 610 x 460mm	Number of flasks	Platform 760 x 460mm	Number of flasks
universal platform	621.250	various	621.450	various
125 ml	621.200	48	621.400	65
250 ml	621.210	35	621.410	40
500 ml	621.220	20	621.420	24
1000 ml	621.230	12	621.430	15
2000 ml	621.240	8	621.440	12

 $We \ reserve \ the \ right \ to \ alter \ specification \ details \ etc. \ without \ prior \ notice \ or \ liability!$



DOMEL, d.o.o., Otoki 21, 4228 Železniki

 BU Laboratory Systems, Na Plavžu 79, 4228 Železniki

 Phone: +386 4 5117 500
 Fax: +386 4 5117 501

 WEB: http://labs.domel.com
 E-mail: info@tehtnica.si