

LABORHITS

LLG-uniTOPDISPENS 2 & 2 Duo

High chemical compatibility

Adjustable dispensing angle flexible

Piston made of PTFE & re-circulation valve

LLG
LABWARE **LLG-uniTOPDISPENS 2**



LLG
LABWARE **LLG-uniTOPDISPENS Duo 2**

- Refilling and rinsing without the need to dismount
- 4 modes of dispensing: Dilution, Rinsing, Dual Liquid Handling and Re-circulation in a single unit



LABORHITS

LLG-uniTOPDISPENS 2 & 2 Duo



- Springless PTFE valve, PTFE piston with chemically resistant ETP O-ring enables high chemical compatibility
- Glass cylinder from borosilicate glass 3.3
- Re-circulation valve enables easy priming and bubble free dispensing
- Smooth, reproducible and effortless dispensing
- 360° rotation possible due to specially designed bottle adapter
- Flexible and adjustable delivery nozzle provides dispensing angle flexibility to the user
- Specially designed volume adjustment knob for quick and easy volume setting
- The telescopic extractable intake tube can be easily adjusted to varying bottle heights
- Nozzle cap reduces contact with air and prevents drying and dripping if the tip cover is attached
- Five bottle adaptors included (28 mm, 32 mm, 37 mm, 40 mm and 45 mm). Standard thread: 30 mm.
- Fully autoclavable at 121 °C, 15 psi for 10 to 15 min
- Individually calibrated in accordance with ISO 8655 standards and each unit is supplied with an individual calibration certificate
- Accuracy max. vol. ($\leq \pm R\%$): 0.6
- Precision max. vol. ($\leq CV\%$): 0.2

LLG-uniTOPDISPENS 2

Volume ml	Graduations ml	PK	Cat. No.
0.25 - 2.5	0.05	1	6.282 275
0.5 - 5	0.1	1	6.282 276
1 - 10	0.2	1	6.282 277
2.5 - 30	0.5	1	6.282 278
5 - 60	1.0	1	6.282 279
10 - 100	2.0	1	6.282 280

LLG-uniTOPDISPENS 2 Duo

Volume ml	Graduations ml	PK	Cat. No.
0.25 - 2.5	0.05	1	6.282 281
0.5 - 5	0.1	1	6.282 282
1 - 10	0.2	1	6.282 283
2.5 - 30	0.5	1	6.282 284
5 - 60	1.0	1	6.282 285
10 - 100	2.0	1	6.282 286

