

## Ultrasonic Cleaner

**Model: ASD-4L**

**Fluxanar Brand / Germany**



### Feature

- All the buttons are touch-sensitive
- Temperature control knob, Max. temperature set up 80°C (cleaning liquid temperature setting), Timer control knob (cleaning time setting), Max. timer set up 30 minutes
- START/PAUSE & Memory button, On/Off button.
- Degas & Sweep button

\*Degassing is the removal of dissolved oxygen trapped in a liquid. In ultrasonic cleaning systems, trapped, dissolved oxygen in the ultrasonic cleaning solution will hinder the ability of the system to clean. This dissolved oxygen must be removed from the system by de-gassing.

\*Sweep function guarantees an optimum sound field distribution in the cleaning bath due to a modulation of the frequencies.

### Specifications

<b>Model</b>	<b>ASD-4L</b>
<b>Ultrasonic power</b>	160 W
<b>Heating power</b>	220 W
<b>Ultrasonic frequency</b>	37 KHz
<b>Drain</b>	No
<b>Tank Vol/Size(mm) L×W×D</b>	4 L/ 302×152×100
<b>Transducer PC</b>	2 x 80w
<b>Timer</b>	30 Min. & Infinity run (4 Hr)
<b>Degassing</b>	Yes
<b>Voltage</b>	220 VAC /50 Hz