



Max Mixing
H₂O 60l



Speed Range
100-2000RPM



Timing Range:
1-999min





Max Viscosity
20000mPa·s



"Set"--Speed,
Timing

- The LED digital tube displays the set speed and actual speed, which is intuitive and clear (LE series)
- DC permanent magnet motor, stepless speed regulation, low noise, maintenance-free, stable operation
- It adopts an open frame, which is suitable for a variety of containers.
- The overload will stop automatically to ensure safe operation.
- Stable start-up, effectively preventing sample overflow.

Product Model	LKS-AT-20L	LKS-AT-40L	LKS-AT-60L	LKS-AT-20LE	LKS-AT-40LE	LKS-AT-60LE
Image						
Voltage (V)	AC100-240					
Frequency (Hz)	50-60					
Power (W)	72	120	200	72	120	200
Timing Range (Min)	/			1-999		
Display Mode	/			Digital Tube		
Speed Range (rpm)	100-2000					
Speed Control Accuracy (rpm)	±5%			±10%		
Max Stirring Volume (H ₂ O) L	20	40	60	20	40	60
Recommended stirring volume (H ₂ O) L	10	20	30	10	20	30
Maximum Stirring Viscosity (mPa·s)	5000	10000	20000	5000	10000	20000
Max Torque (N·cm)	10	20	30	10	20	30
Motor Type	DC Permanent Magnet Motor					
Working Environment	5-40℃ , 80%RH					